



Intermec

Product Profile



- First RFID printer to encode frequency agile UHF tags
- Encodes and prints RFID labels without host system reprogramming
- Simultaneously print barcodes, human readable text, and graphics
- Supports stand-alone printer applications
- Integrated EasyLAN™ Ethernet, USB, and serial interface standard
- Optional EasyLAN™ Wireless interface

INTELLITAG® PM4i PRINTER

The multi-function Intellitag PM4i printer gives you the reliability, ruggedness and performance you have come to expect in a barcode printer from Intermec, along with the latest RFID technology in the same box.

With the Intellitag PM4i, companies can create RFID smart labels to drive RFID applications without host reprogramming. By using frequency agile RFID tags, the Intellitag PM4i can simultaneously encode and print labels that can be used worldwide, thus enabling the tag to be read via multiple frequencies, dependant on regional standards.

The Intellitag PM4i printer can also act as a "smart client" executing user-defined programs for completely stand-alone printer applications. This means your Intellitag PM4i printer can eliminate the personal computer, operate additional hardware (e.g. scanners, other printers, conveyors), access information from network host, and retain the ability to change with the application for additional functionality.

Integrated EasyLAN™ Ethernet, USB, and serial are standard interfaces with the Intellitag PM4i printer. Users also have the option to add additional EasyLAN Wireless and / or industrial interface boards. The EasyLAN Wireless interface uses an integrated standard 802.11b radio. This radio provides 128-bit WEP encryption of the information relayed through the network. Intermec's wired and wireless technology ensures secure printing and network infrastructure for all environments.

The Intellitag PM4i printer integrates into industrial manufacturing, warehouse, and logistics applications ensuring all items are labeled and tracked via RFID for quick and accurate data collection throughout the supply chain.

Intermec

Application

Direct Thermal and Thermal Transfer label, ticket and tag printer.

Physical Characteristics

Length: 54.3 cm (21.38 in)

Height: 26.1 cm (10.28 in)

Width: 29.8 cm (11.73 in)

Weight: 13.5 kg (29.76 lbs.)

Print Specifications

Max. Width: 104 mm (4.09 in) at 203 dpi; 105.7 mm (4.16 in) at 300 dpi.

Max. Length w/ std memory: 2520 mm (99.2 in) at 203 dpi; 1092 mm (43.0 in) at 300 dpi.

Max length w/ 16MB SDRAM: 4095 mm (161.2 in) at 203 dpi; 2730 mm (107.5 in) at 300 dpi.

Print Speed

Up to 76 labels per minute. 101x152mm (4x6 in) GM1724 label. To learn more about print speed, please visit www.intermec.com/printspeed.

Print Direction

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

Print Resolution

8 dots/mm (203 dpi); 11.8 dots/mm (300 dpi)

Label/Ticket/Tag

Max. Width: 114.3 mm (4.5 in)

Min. Width: 25.4 mm (1 in)

Thickness: 2.5 to 7 mil

Style: Roll-fed, die-cut, continuous or fanfold labels, tags or tickets

Label Roll max diameter: 213 mm (8.38 in)

Label Roll Core: 38-76 mm (1.5-3 in)

Media Type: Thermally sensitive media

Ribbon Roll

Ribbon roll max diameter: 83 mm (3.27 in) or approx. 450 m (1475 ft) of ribbon

Ribbon Roll Core: 25 mm (1 in)

Ribbon Type: Wax, wax/resin, resin

Intellitag Label Specifications

Tag thickness: Less than .25 ml (.010 in)

Tag insert size: 13ml x 70ml (.5 in x 3 in); 95ml x 95ml (3.75 in x 3.75 in)

Tag placement: Between label and backing paper, location within label customized for each application.

Tag orientation: Perpendicular to feed direction.

Interface Standard

- RS-232, up to 115.2 kB/s
 - USB 1.1
 - EasyLAN Internal Ethernet 100/10BaseT
 - I2C-bus for cutter
 - Wand interface for EasySet™ System
- Optional**
- EasyLAN Wireless, internal 802.11b Wireless Ethernet
 - Parallel IEEE 1284

Software

Available printer command languages:

- IPL
 - Fingerprint/Direct Protocol
- Software Development Kit:** A custom Fingerprint program to interface with RFID module and host system is easily generated through the use of Intermec Fingerprint ApplicationBuilder (IFAB), a software development kit for Fingerprint with RFID libraries.

Bar Code Symbolologies

1-dimensional: Code 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Interleaved 2 of 5, Straight 2 of 5, Matrix 2 of 5, Postnet, Code One, UPC/EAN, JIS-ITF

2-dimensional: Code 16K, Code 49, DataMatrix, PDF417, QR Code, MicroPDF417, MaxiCode, Plessey, MSI

Standards Supported

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

Characters Sets

Fingerprint/DP: 15 TrueType™ fonts including 12 UNICODE (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. All fonts are scalable. Font cache for maximum performance. ATF font support.

IPL firmware: 3 TrueType fonts and 20 bitmap fonts.

Non-Latin fonts are available as options.

Graphics

Supports PCX file format.

Memory

Standard: 4MB Flash

Optional: Additional FLASH memory up to 16 MB (8+8); 1 GB Compact Flash Memory

Protocol

Fingerprint/Direct Protocol:

XON/XOFF, ENQ/ACK, DTR, RTS/CTS

IPL: XON/XOFF, Intermec Std. Protocol

Display

Back-lit LCD for 2x16 characters and 3 LED indicator lamps

Keypad Control Panel

- Full keypad control panel (Fingerprint/DP)
- Reduced keypad control panel (IPL)

Power Supply

115/230VAC auto-switch w/PFC

Voltage range: 90-264VAC.

Frequency Range: 45-65 MHz

Operating Environment

Temperature: +5°- 40°C (+40°- 104°F)

Humidity: 20-80% RH non-condensing

Noise: 50 dB (printing), no noise standby

Regulatory Approvals

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Options

Integral Self-Strip unit with Liner Takeup, Label Taken Sensor (LTS), Compact Flash (CF) memory, Flash and SDRAM SIMM memory, Various International Double Byte Fonts, EasySet Bar Code Wand*, External RS-232C Alphanumeric Keyboard*, Parallel Interface Board, Real Time Clock*, Media Supply Hub, Cutter, Label Low Sensor

*Not applicable when using IPL firmware

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/ Middle East & Africa Headquarters

Sovereign House
Vestern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Intermec International Inc.
14 Floor, IBM-Pacific Century Plaza
2A Workers Stadium
Chaoyang District, Beijing 100027
P.R. China
Tel: +86 (010).6539 1012
Fax: +86 (010).6539 1025

Australia

Level 7, 200 Pacific Highway
Crowns Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

South America & Mexico

Intermec South America Ltda.
Rua Arandu 1544-15 andar
Edificio Itavera
Brooklin Novo 04562-031
Sao Paulo, SP
Brazil
tel: 55.11.5501.2070

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.211.1919
fax: 525.55.211.8121

Worldwide

**Fax Document
Retrieval Service**
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611518-01A 02/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.