

# HX3

## Rugged Voice Computer

LXE | FLEX | Wearable Computers



The HX3 voice computer is truly an open system, non-proprietary device. It gives voice integrators a perfect platform for deploying voice-centric applications. Built with ToughTalk™ technology, a specialised combination of LXE's trademark rugged system design, advanced audio circuitry and noise-canceling techniques, the HX3 offers high quality speech exchange capabilities in the harshest environments, even in cold stores at -40°C.

The lightweight HX3 computer is designed to be 'forgotten' by the operative using it, by offering a natural interaction with the voice-driven logistics system.

A simple programmable keypad executes common tasks easily. The HX3 hands-free computer also supports wired and wireless headsets, barcode scanners and imagers for multimodal applications. And like all LXE computers, the HX3 is Born Rugged, Not Made Rugged™.



### RUGGEDNESS

Magnesium alloy bezel with high impact case for survival in harsh environments.

### COMFORT

Small, light-weight design offers comfort for full-shift operations. Large Eyes-Free Keyboard simplifies common tasks.

### OPEN TECHNOLOGIES

- 802.11b/g radio.
- Windows® CE 5.0 OS.
- Bluetooth 2.0+EDR.



IP 54



-40°C



1.2 m



VOICE READY



# HX3

## TECHNICAL SPECIFICATIONS



### PLATFORM

#### Processing & Memory

- PXA255 400MHz
- 128MB SDRAM
- 128MB or 512MB Flash

#### Operating System

- Windows® CE 5.0 Professional Plus
- Non-volatile storage of resident drivers, applications and settings

#### Eyes-Free Keyboard™

- 4 large keys with hard caps for long life and abrasion protection
- 3 functional keys + 1 modifier key allows 3 one-touch keys and 3 two-touch keys
- Unique key shapes for easy Eyes-Free navigation
- Keyboard mapping support

#### Power System & Management

- 12-hr standard battery (w/typical use)
- 24-hr extended battery (w/typical use)
- Batteries are remotely tethered for added flexibility and comfort
- Backup battery w/automatic charging for main battery hot swap
- Active power management (configurable)

#### Enclosure

- Magnesium alloy bezel with high impact plastic case
- Dimensions: 12.6cm x 8.9cm x 3.6cm
- Weight:
  - HX3 - 264g
  - SR laser ring - 42g
  - Standard battery - 130g

### CONNECTIVITY

#### Software

- Barcode wedge, RF, audio mixer, power management and diagnostic utilities
- SDK with Microsoft® & LXE APIs
- Support VoIP (PTT) and voice recognition software

#### Optional Software

- RFTerm® (VT220, TN5250, TN3270)
- AppLock utility controls user application-access & unwanted configuration changes
- Personal JAVA 1.2 JVM
- Localisation for English, simplified Chinese, traditional Chinese, Korean, Thai and Japanese
- Barcode wedge, RF, audio mixer, power management and diagnostic utilities

#### Interfaces

- Ring-scanner interface
- Built-in microphone & speaker for VoIP
- Speaker supports >102 dB volume
- Headset interface for voice recognition and VoIP
- USB host, USB client, RS-232 through cradle
- Power input

#### Radio Card Support

- 802.11b/g (2.4GHz)
- 802.11a/b/g (2.4GHz & 5GHz)
- 802.11b/g (2.4GHz) + Bluetooth
- WPA, WPA 2
- Optimized internal diversity antenna
- Bluetooth 2.0+EDR class 2 radio

### RUGGEDNESS

#### Environmental

- Temperature rating
  - Cold start down to -20°C
  - Operation in freezers to -40°C when worn under an outer garment.
  - Maximum operating temperature 50°C
- Humidity Operating:
  - 5% to 90%RH non-condensing at 40°C
- Drop Specification: 1.2m multiple drops to concrete
- Ingress protection enclosure rating:
  - IEC 60529 compliant to IP54

#### Approvals

- Emissions (EMI)
  - FCC Part 15 Subpart B, Class A
  - Industry Canada ICES-003 Class A
  - EN 55022, Class A (CISPR22)

- Immunity (EMC)EN 55024:1998
- Safety
  - UL 60950CSA C22.2 No. 60950EN 60950, IEC 60950
- Laser SafetyCDRH:
  - 21 CFR 1040.10, EN 60825-1 and IEC 60825-1
- Radios separately approved to:
  - FCC Part 15, Subpart C
  - IndustryCanada RSS 210, RSS 102, RSS 139 and/or 210
- R&TTE Directive:
  - EN 300 328, EN 300 826, EN 60950FCC Part 15 Subpart B, Class A Industry Canada ICES-003 Class A
- RoHS-compliant

### DATA CAPTURE

#### Bar Code Ring Scanner

- SR laser ring - 45" scan distance Available w/long cables to attach to hip flip or voice case
- 2D imager ring - 21" scan distance Available w/long cables to attach to hip flip or voice case
- Enhanced white LED flash illumination

### ACCESSORIES

#### Wearable Accessories

- Belt-mounted hip-flip
- Belt-mounted voice case

#### Other Accessories

- 6 bay battery charger w/analyzer
- Desktop cradle - powers HX3 computer, 2 battery charging slots, USB host, USB client and RS-232
- ActiveSync cable (does not require cradle)

- Headset adapter cable
- Replacement battery cable
- Battery extension cable (allows battery to be worn a greater distance from the HX3)
- USB host cradle cable
- USB client cradle cable
- RS-232 cradle cable

Download accessory catalogue at [www.lxe.com](http://www.lxe.com)



#### LXE AMEA

60 Alexandra Terrace, #03-23  
The Comtech  
Singapore 118502  
Phone: +65 6278 0593  
E-mail: [info.singapore@lxe.com](mailto:info.singapore@lxe.com)  
[www.lxe.com](http://www.lxe.com)



#### LXE Gamma Solutions Pty. Ltd.

Office in Melbourne, Sydney, Brisbane, Adelaide & Perth  
Phone: 13 000 GAMMA (1300 042 662)  
[www.gammasolutions.com](http://www.gammasolutions.com)