

Preliminary  
Product profile



# SF61B

Mobility Scanner for  
Healthcare Applications



#### ERGONOMIC

Compact size can be quickly and can be securely stowed in a smock pocket, on a belt loop, or along the arm—for unencumbered use of both hands



#### HEALTHCARE

Disinfectant-ready housing with IP65 seal rating protects against the harmful effects of repeated chemical wipe-downs



#### LASER-FREE

Completely safe laser-free design with LED aimer is ideal for patient-facing applications



#### SCANNING

Includes the industry's fastest 2D imaging technology for highly responsive, omni-directional scanning even on curved or shiny surfaces



#### RADIO

Bluetooth® wireless pairs easily with iOS®, Android® and Windows Mobile® devices, with a range of up to 100 m (325 ft)



#### BATTERY

Field-replaceable battery provides greater than full-shift battery life, even in scan-intensive applications

Consistent, accurate data capture is fundamental to patient safety and cost-effective healthcare operations, yet traditional gun-shaped handheld scanners were not designed to move with the worker. To address this challenge and make it easier to collect data at the point of care, we developed the SF61B healthcare mobility scanner. Small enough to stow in a pocket, it travels with the worker and can be quickly accessed or securely tucked away when unencumbered use of both hands is required. This makes it ideal for today's busy healthcare environment, where complete freedom of movement is essential and occasional scanning is required.

The SF61B easily integrates with existing healthcare information management systems and—with integrated Bluetooth wireless—easily pairs with iOS, Android and Windows Mobile smartphones and tablets. Its compact form factor is small enough to fit into awkward or constricted spaces, and a high performance imager makes it easy to scan all 1D and 2D codes—regardless of angle or orientation. High motion tolerance (up to 400 in/sec

and omni-directional reading capability result in extremely responsive, hassle-free scanning. And to ensure totally safe operation in patient-facing applications, the SF61B uses a laser-free design that provides this high performance scanning capability without the risk of eye injury.

As a mobility scanner, the SF61B was engineered for all-day wireless performance. An integrated Bluetooth Class 1 radio enables wireless communication at ranges up to 100 m (325 ft) from the host, and its field-replaceable battery lasts well beyond a full shift, even in the most scan-intensive applications.

The SF61B is also highly customizable to complement your healthcare environment. With our free EasySet™ PC programming tool, you can adjust security settings, beeper volume, and even enable haptic feedback (vibration profiles) for quiet hospital settings where audible tones are not desired. When you're satisfied with the settings, simply create a configuration bar code to quickly program additional scanners to match.

## Physical Characteristics

**Dimensions (LxWxH), including ring end-cap:**  
16.0 cm (6.3 in) x 4.6 cm (1.8 in) x 3.9 cm (1.5 in)  
**Weight:** 184 gm (6.5 oz)

## Electrical Specifications

**Battery:** Lithium-ion rechargeable (2,600 mAh)  
**Battery Life<sup>1</sup>:** 28,000 scans (1D) or 25,000 scans (2D), with 1 scan every 4 seconds<sup>2</sup>  
**Recharging Time:** 3 hours  
<sup>1</sup>Battery life may vary depending on ambient temperature, ambient light and battery life.  
<sup>2</sup>Typical number of scans possible without a battery recharge, in a typical office environment (250 lux) at ambient temperature.

## Bluetooth Radio

**Type:** Bluetooth Class 1 v2.1+EDR  
**Frequency:** 2.4 GHz with Adaptive Frequency Hopping  
**Range:** 100 m (325 ft) in open space, 30 m (100 ft) in typical work environment  
**Profiles:** HID, SPP

## Connectivity

**Operating System Compatibility:** Apple iOS®; Google Android®; Microsoft Windows® XP, Vista, 7, 8

## Scan Technology

Intermec Area Imager with LED Aimer (EA31)

## Reading Performance

**Maximum Code Resolution:**  
1D: 4 mils  
2D/HP: 6.6 mils  
**Print Contrast:**  
1D: 25%  
2D/HP: 20%  
**Motion Tolerance:** Up to 400 in/s

## User Feedback

- Indicator LED
- Configurable buzzer
- Configurable vibrator (haptic feedback)

## 1D Bar Code Symbolologies Supported

Codabar, Code 11, Code 39, Code 93/93i, Code 128 / GS1-128, EAN/UPC, GS1 DataBar Limited, GS1 Composite (linear only), GS1 DataBar Expanded, GS1 DataBar limited, GS1 DataBar Omnidirectional, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, Standard 2 of 5, Telepen

## 2D Bar Code Symbolologies Supported

DataMatrix, QR Code, Micro QR, PDF417, Micro PDF417, Aztec, Maxicode, Han Xin, Codablock A, Codablock F, GS1 Composite, TLC 39

## Postal Bar Code Symbolologies Supported

Australian Post, BPO, Canada Post, Dutch Post, Infomail, Intelligent Mail, Japan Post, Planet, Postnet, Sweden Post

## Environment

**Housing:** Disinfectant ready  
**Operating Temperature:** -20°C to +50°C (-4°F to +122°F)  
**Storage Temperature:** -40°C to +70°C (-40°F to +158°F)  
**Charging Temperature:** 0°C to 45°C (32°F to 113°F)  
**Relative Humidity:** 5 to 95% non-condensing  
**Drop:** 26 drops from 2m (6.5 ft.) to concrete  
**Environmental Rating:** IP65  
**Ambient Light:** 0 to 100,000 lux

## Electromagnetic Emissions Standards

Meets the requirements of the following product emission standards:

- FCC Part 15 Class B (United States)
- Industry Canada ICES-003 Class B (Canada)
- R&TTE: CISPR 22 Class B (European Union)

## Environmental Compliance Requirements

Conforms to environmental compliance requirements for RoHS, China RoHS, WEEE, and REACH.

## Regulatory Approvals

UL; CE Mark (EU)

## Standard Warranty

Three year standard warranty, with extended protection available through Intermec Medallion Support Services.

## Accessories

View the SF61B Accessory Guide for complete details.

- Single Bay Charger\*
- Four Bay Charger\*
- Belt Clip Holder\*
- Industrial Belt Clip Holder\*
- Chest Strap Holder\*
- Wireless Base Station\*
- Flexdock Four-Bay Charger
- Flexdock Cup
- In-Vehicle Power Adapter
- Ring End-Cap With Wrist Strap
- Easyset™ Configuration Software

\* These accessories are backward compatible with SF51.

## North America

**Corporate Headquarters**  
6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348 2600  
Fax: (425) 355 9551

## North Latin America

**Headquarters Office**  
Mexico  
Phone: (+52) 55 52 41 48 00  
Toll Free NOLA:  
01800 490 4990

## South Latin America

**Headquarters Office**  
Brazil  
Phone: (+55) 11 3711 6776  
Fax: (+55) 11 5502 6780

## Europe, Middle East & Africa

**Headquarters Office**  
Reading, United Kingdom  
Phone: (+44) 118 923 0800  
Fax: (+44) 118 923 0801

## Asia Pacific

**Headquarters Office**  
Singapore  
Phone: (+65) 6303 2100  
Fax: (+65) 6303 2199

## Media Sales

EMEA: (+31) 24 372 3167  
USA: (513) 874 5882  
<http://intermec.custhelp.com>

## Sales

Toll Free NA: (800) 934 3163  
Toll in NA: (425) 348 2726  
Freephone ROW:  
00800 4488 8844

## OEM Sales

Phone: (425) 348 2762

## Customer Service and Support

Toll Free NA: (800) 755 5505  
Toll in NA: (425) 356 1799  
EMEA: [intermec.custhelp.com](mailto:intermec.custhelp.com)

## Internet

[www.intermec.com](http://www.intermec.com)

## Worldwide Locations

[www.intermec.com/locations](http://www.intermec.com/locations)

Copyright © 2013 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners.  
612289-A 06/13

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

